

# Ø500 外转子轴流风机 Axial Fans







## 使用说明:

工作方式: S1  
 绝缘等级: B级 F级  
 环境温度: -30℃ ~ 60℃

## 应用范围:

4D-500 380V/50Hz 0~90Pa (20Pa-6300m³/h)  
 4E-500 220V/50Hz 0~90Pa (20Pa-6000m³/h)  
 6D-500 380V/50Hz 0~90Pa (20Pa-4350m³/h)  
 6E-500 220V/50Hz 0~90Pa (20Pa-4400m³/h)



			VOLTAGE 额定电压 V	FREQUENCY 频率 Hz	CURRENT 额定电流 A	INPUT 输入功率 W	SPEED 额定转速 r/min	AIR VOLUME 额定风量 m³/h	CAPACITANCE 电容 μF	NOISE 噪音 dB(A)	NET WEIGHT 净重 kg	LICENSE 证书	NO. ON THE CURVE
YWF-4D-500-S-137/35-G	YWF-4D-500-S-137/35-T	YWF-4D-500-S-137/35-B	380	50	0.9	450	1300	6570	/	72	9.0	CCC CE	1
YWF-4E-500-S-137/35-G	YWF-4E-500-S-137/35-T	YWF-4E-500-S-137/35-B	220	50	1.95	420	1300	6420	10	72	9.0	CCC CE	2
YWF-6D-500-S-137/35-G	YWF-6D-500-S-137/35-T	YWF-6D-500-S-137/35-B	380	50	0.55	230	900	4840	/	68	9.0	CCC CE	3
YWF-6E-500-S-137/35-G	YWF-6E-500-S-137/35-T	YWF-6E-500-S-137/35-B	220	50	1.15	230	900	4830	10	68	9.0	CCC CE	4

